

Additional guidance on the acceptance of solid premixed bulk waste for recovery (operation R1)

As a general rule, the general acceptance criteria for the bunker must be observed when accepting solid premixed waste in bulk (Customer Information D1129 Instructions On The Disposal Of Solid Waste Mixtures Hazardous Waste Incineration).

kontakt@gsb.bayern
www.gsb.bayern

In addition, the following requirements apply to thermal recovery:

European Waste Code	Premixed solid waste is classified under waste codes in chapter 19 of the Annex to the Regulation. In particular EWC 19 02 04*, 19 02 09*, 19 12 11*.
max. particle size	< 40 cm
pH value	5 – 12
Calorific value	> 11.000 kJ/kg
Mercury (Hg), Arsenic (As)	< 10 ppm
Cadmium (Cd), Thallium (Tl)	< 100 ppm
Molybdenum (Mo), Nickel (Ni)	< 600 ppm
Antimony (Sb), Lead (Pb)	< 1.000 ppm
PCB (as per LAGA = DIN value * 5) /PCP/PCT	< 50 mg/kg
Dioxins/Furans	none
Cyanides (CN ⁻)	< 50 mg/kg
Cyanide easily released	none
Sulphide (S ²⁻)	< 50 mg/kg
Sulphide (S ²⁻) easily released	none
Fluorine (F)	< 0,5 %

Vertrieb
Äußerer Ring 50
85107 Baar-Ebenhausen
Fon 0 84 53 / 91-241
Fax 0 84 53 / 91-230
E-Mail:
vertrieb@gsb.bayern

D1168_EN/ Revision: 01
Stand: 07/2026

KUNDEN-Information

Chlorine (Cl)	< 5 %
Bromine (Br)	< 0,2 %
Iodine (I)	< 0,1%
Sulfur (S)	< 2 %
Form of delivery	Bulk (roller container, skip container, tipping semi trailer)

Any derogation from these criteria has to be agreed upfront with GSB.

Relevant documents

- F0358 Waste Profile
- D1129 Instructions On The Disposal Of Solid Waste Mixtures (Hazardous Waste Incineration)